

# TEL - SPLICING MATERIAL

## For Fabric Ply Belting

### Adhesives

Item	Sp.Gr	Packing
T-4451	0.90 ± 0.03	1Kg, 5Kg, 20Kg
TH-4451	1.20 ± 0.03	1Kg, 5Kg, 20Kg
TF-4451	1.40 ± 0.03	1Kg, 5Kg, 20Kg

### Hardener Compound

Item	Sp.Gr	Packing
THC <sup>o</sup>	1.30 ± 0.05	60gms, 500gms, 1Kg
THC-HR <sup>o</sup>	0.99 ± 0.03	60gms, 500gms, 1Kg

#### Note:

- T - M-24 Grade materials.
- TH - Heat resistant materials, withstanding upto 170°C
- TF - Non Inflammable materials and capable of withstanding upto 120°C
- THC - Hardener compound for hot splicing of conveyor belt grades M24, HR and SHR
- THC-HR- Hardener compound for hot splicing of conveyor belt grades HR and SHR
- ① - The proportion for use with T, TF and TH grades differ. Please refer our instruction manual

### Cover Compounds

Item	Std. Dimension	Std. Packing
TCC-151	A,B	1.5Kgs, 20Kgs
TCC-151H	A,B	1.5Kgs, 20Kgs
TCC-151F	A,B	1.5Kgs, 20Kgs

### Insulation Compounds

Item	Std. Dimension & Packing	Std. Packing
TIC-151	C	1.5Kgs
TIC-151H	C	1.5Kgs
TIC-151F	C	1.5Kgs

#### Note : The standard sizes are as given below

- A. 150mm wide × from 1.5mm to 4mm thick
- B. 500mm wide × from 1.5mm to 4mm thick
- C. 150mm wide × from 0.35mm to 0.60mm thick

### Accessories

Non Stick Agents	Packing
TNS-40	500gms, 1 Kg, 20Kg
Cleaning Fluid	Packing
TCF-40	500gms, 1 Kg
Release Fabric	Packing
TPC-40	Running lengths

**NOTE : All the specifications given above are subject to change.**