

SR-50

SKIRT SEALING RUBBER

TEL SR-50 SKIRT SEALING RUBBER is a simple, cheap yet effective skirting system that prevents dust and spillage and reduce clean-up and maintenance costs at installations.

It is a pre-moulded rubber sheet made from proprietary formulations of Natural with Synthetic rubber blends. It can easily be fitted to your existing chute walls with the help of a clamping system. Clamping system is not part of the standard supply and can be supplied on request. The skirt rubber is available in many sizes and thickness to suit various working conditions. Standard Sealing strips come in lengths of 10 meter, how ever customized lengths(Max 50 mtr) can be supplied on request.



SALIENT FEATURES

- Economic solution for spillage and dust control.
- Optional Quick Release clamp for easy installation and adjustment.
- Superior Rubber Compound offers excellent wear resistance and very low-abrasion.
- Available in Standard width of 1500mm & 2000mm and thickness 10mm, 12mm, 15mm & 20mm.
- Custom sizes available on demand.

PART NO. & DIMENSIONS

Assembly P/N*	Thickness In. (mm)	Width In. (mm)	Length Ft. (M)
TSR50-10-15-X	0.4 (10)	60 (1500)	32 (10)
TSR50-10-20-X	0.4 (10)	80 (2000)	32 (10)
TSR50-12-15-X	0.5 (12)	60 (1500)	32 (10)
TSR50-12-20-X	0.5 (12)	80 (2000)	32 (10)
TSR50-15-15-X	0.6 (15)	60 (1500)	32 (10)
TSR50-15-20-X	0.6 (15)	80 (2000)	32 (10)
TSR50-20-15-X	0.8 (20)	60 (1500)	32 (10)
TSR50-20-20-X	0.8 (20)	80 (2000)	32 (10)

* Replace X with 'B' for Black & 'O' for Orange colour skirt

SPECIFICATIONS

Colour	Hardness (Shore A)	Tensile Strength (Kg/Sq. Cm)	Elongation at Break (% Min)	Abrasion Loss (Cu. mm)
Black	50 +/- 5	110	600	160
Orange	50 +/- 5	90	550	160

THEJO offers a complete package including design, supply, consultancy, technical support, service back-up and maintenance to assure that our clients will obtain the best benefits at the lowest cost for any trouble shooting and improvement needed in the plant.

* For more information please contact your nearest Thejo representative.