

WARHOG[®] 50WT & 50W

Wet Abrasion Resistant Sheets

WARHOG 50WT & 50W are wine red coloured sheeting made out of a proprietary rubber composition containing Natural & Synthetic Rubber. These sheets are subject to controlled production parameters from compounding, mixing, calendering & high pressure molding process. These sheets deliver good properties of impact, strength, cut & tear resistance against slurry handling application. They are formulated in relatively higher hardness so as to take care of impact & abrasion caused while handling coarse particles also. WARHOG is ideal for medium duty application and is a cost competitive version of WARDOG sheets.



SALIENT FEATURES

- Good properties to combat high Impact & Abrasion of slurry having coarse particle
- Good abrasion resistant values
- Good contour ability
- Knit surface to enhance bonding strength
- Special tacky bonding layer
- Precision moulded and press cured ensures
- consistent dimensional and physical properties.

APPLICATION

Slurry handling areas such as:

- Pipe lining
- Chute lining
- Pump boxes & Tank lining
- Launder lining
- Hydro cyclones
- Hoses etc.



WARHOG 50WT has tacky bonding layer to facilitate better bonding results when applied to metal with cold bonding adhesive.

WARHOG 50W does not posses tacky bonding layer, but has a knit surface finish to enhance bonding results when applied to metal with cold bonding adhesive.

SPECIFICATIONS

Properties	Value		
Hardness	50 ± 5 Shore A	ASTM D2240	
Specific Gravity	1.00 ± 0.03	ASTMD 792	
Tensile Strength (Min)	125 Kg/cm2	ASTM D412	
Elongation at break (Min)	650 %	ASTM D412	
Tear Strength (C type) (Min)	17Kg/cm	ASTM D624	
Abrasion Loss @ 10 N (Max)	165 mm3	DIN53516	

STANDARD SIZES

PART NO	ITEM DESCRIPTION	LENGTH mm	WIDTH mm	THICK mm	BONDING LAYER	FINISH	COLOUR
WH-10-1.5-3-50-WT	WARDOG 50WT	10000	1500	3	ΤΑСКΥ ΒΑСΚ	GLOSSY	WINE RED
WH-10-1.5-6-50-WT	WARDOG 50WT	10000	1500	6	ΤΑϹΚΥ ΒΑϹΚ	GLOSSY	WINE RED
WH-10-1.5-10-50-WT	WARDOG 50WT	10000	1500	10	ΤΑСКΥ ΒΑСΚ	GLOSSY	WINE RED
WH-10-1.5-12-50-WT	WARDOG 50WT	10000	1500	12	ΤΑСКΥ ΒΑСΚ	GLOSSY	WINE RED

PART NO	ITEM DESCRIPTION	LENGTH mm	WIDTH mm	THICK mm	BONDING LAYER	FINISH	COLOUR
WH-10-1.5-3-50-W	WARDOG 50W	10000	1500	3	NIL, KNIT SURFACE	GLOSSY	WINE RED
WH-10-1.5-6-50-W	WARDOG 50W	10000	1500	6	NIL, KNIT SURFACE	GLOSSY	WINE RED
WH-10-1.5-10-50-W	WARDOG 50W	10000	1500	10	NIL, KNIT SURFACE	GLOSSY	WINE RED
WH-10-1.5-12-50-W	WARDOG 50W	10000	1500	12	NIL, KNIT SURFACE	GLOSSY	WINE RED

Note: Other sizes will be available on request. Kindly confirm prior to the ordering.

Dimensional tolerance : As per ISO-3302-1, first edition 1996-07-15, moulding - class M3 standards.

ADHESIVE SYSTEMS

- Primer : TPR 1400
- Adhesive : TC310 , TBS 3000, TBS 3001 with corresponding hardener compound.

Note: Kindly refer our adhesive program.

STORAGE

Recommended to keep away from direct sunlight and temperature as per "ISO 2230, Vulcanised Rubber" guidelines.

* For more information please contact your nearest Thejo representative.





GLOBAL NETWORK • Australia • Brazil • Chile • India • Saudi Arabia