

# WARHOG® 60WT & 60W

## Wet Abrasion Resistant Sheets

**WARHOG 60WT & 60W** are wine red coloured sheeting made out of a proprietary rubber composition containing Natural & Synthetic Rubber. These sheets are subject to controlled production parameters from compounding, mixing, calendaring & high pressure molding process. These sheets deliver good properties of impact, strength, cut & tear resistance against extreme slurry handling wet as well as dry application. They are formulated in higher hardness so as to take care of impact & abrasion caused while handling coarse particles. WARHOG is ideal for medium duty application and is a cost competitive version of WARDOG sheets.



### SALIENT FEATURES

- Good properties to combat high Impact & Abrasion of slurry having coarse particle
- Good abrasion resistant values
- Good contour ability
- Knit surface to enhance bonding strength
- Special tacky bonding layer
- Precision moulded and press cured ensures
- consistent dimensional and physical properties.

### APPLICATION

*Slurry handling areas such as:*

- Pipe lining
- Chute lining
- Pump boxes & Tank lining
- Launder lining
- Hydro cyclones
- Hoses etc.

**WARHOG 60WT** has tacky bonding layer to facilitate better bonding results when applied to metal with cold bonding adhesive.

**WARHOG 60W** does not possess tacky bonding layer, but has a knit surface finish to enhance bonding results when applied to metal with cold bonding adhesive.

### SPECIFICATIONS

Properties	Value	
Hardness	60 ± 5 Shore A	ASTM D2240
Specific Gravity	1.00 ± 0.03	ASTMD 792
Tensile Strength (Min)	130 Kg/cm <sup>2</sup>	ASTM D412
Elongation at break (Min)	550 %	ASTM D412
Tear Strength (C type) (Min)	18Kg/cm	ASTM D624
Abrasion Loss @ 10 N (Max)	155 mm <sup>3</sup>	DIN53516

## STANDARD SIZES

PART NO	ITEM DESCRIPTION	LENGTH mm	WIDTH mm	THICK mm	BONDING LAYER	FINISH	COLOUR
WH-10-1.5-3-60-WT	WARDOG 60WT	10000	1500	3	TACKY BACK	GLOSSY	WINE RED
WH-10-1.5-6-60-WT	WARDOG 60WT	10000	1500	6	TACKY BACK	GLOSSY	WINE RED
WH-10-1.5-10-60-WT	WARDOG 60WT	10000	1500	10	TACKY BACK	GLOSSY	WINE RED
WH-10-1.5-12-60-WT	WARDOG 60WT	10000	1500	12	TACKY BACK	GLOSSY	WINE RED

PART NO	ITEM DESCRIPTION	LENGTH mm	WIDTH mm	THICK mm	BONDING LAYER	FINISH	COLOUR
WH-10-1.5-3-60-W	WARDOG 60W	10000	1500	3	NIL, KNIT SURFACE	GLOSSY	WINE RED
WH-10-1.5-6-60-W	WARDOG 60W	10000	1500	6	NIL, KNIT SURFACE	GLOSSY	WINE RED
WH-10-1.5-10-60-W	WARDOG 60W	10000	1500	10	NIL, KNIT SURFACE	GLOSSY	WINE RED
WH-10-1.5-12-60-W	WARDOG 60W	10000	1500	12	NIL, KNIT SURFACE	GLOSSY	WINE RED

Note: Other sizes will be available on request. Kindly confirm prior to the ordering.

Dimensional tolerance : As per ISO-3302-1, first edition 1996-07-15, moulding - class M3 standards.

## ADHESIVE SYSTEMS

- Primer : TPR 1400
- Adhesive : TC310 , TBS 3000, TBS 3001 with corresponding hardener compound.

Note: Kindly refer our adhesive program.

## STORAGE

- Recommended to keep away from direct sunlight and temperature as per "ISO 2230, Vulcanised Rubber" guidelines.

\* For more information please contact your nearest Thejo representative.